

 SERIES

Hytera 



AVAILABLE THROUGH:

Sure-Response

Tel: 888.530.5668
1075 North Reed Station Road
Carbondale, IL 62902
www.sure-response.com



Pocket-Size Digital Portable Radio


PD362 SERIES



- Pocket-Sized Design with Easy Charging Through Micro-USB
- Analog / Digital Dual Mode Operation for Easy Transition to Digital

DMR RATED
EMERGENCY MOBILITY RADIO ASSOCIATION
IP54

www.hytera.us



The Hytera PD362i is an open-standard DMR radio capable of providing quality voice communication in a small pocket-sized design approved to IP54 and MIL-STD 810 testing. The 2000 mAh long lasting battery yields approximately 12 hours under a 5-5-90 duty cycle in digital mode. This is the ideal radio solution for small organizations looking for a cost-effective way to migrate to clear digital communication.

AVAILABLE THROUGH:



Sure-Response

Tel: 888.530.5668
 1075 North Reed Station Road | Carbondale, IL 62902
www.sure-response.com

Applications

- Retail
- Malls
- Restaurants
- Hotel
- Events
- Warehouse
- Education
- Executives



Product Features

- Pocket Size Design**
 The monochrome display allows good visibility even under extremely strong light. The compact antenna design and light weight PC & Metal frame design. The PD362i is 4.84 x 2.17 x 0.91 inches weighing 5.64oz.
- Micro USB Port**
 The Micro USB port allows you to use a standard USB to Micro USB to charge the radio
- Compact Antenna**
 The creative and compact antenna design makes the PD362i sleek and gives it a cellular phone feel
- Monochrome Display**
 Two line display with monochrome color and supports messaging with up to 64 characters.
- Dual Mode: Analog & Digital**
 Dual mode (analog & digital) operation ensures a smooth analog to digital migration.
- Scan**
 Capable of scanning of pure analog voice and signaling, pure Digital voice and data.
- Mixed Mode RX**
 Allows the radio to monitor both analogue and digital calls on a single frequency.
- Versatile Voice Calls**
 The intelligent signaling supports various voice call types, including Private Call, Group Call, and All Call.
- Various Analog Signaling Types**
 Various analog signaling types various squelch control types (CTCSS / CDCSS), thus providing higher function expansion capacity to the analog world.
- Additional Features**
 Voice Calls - Private, Group Call and ALL CALL
 Pre-programmed text messages
 Pseudo Trunk operation & Basic Encryption (via license)
 Remote Monitor, Radio enable / disable and Priority Interrupt (via license)
 Radio Registration Service (RRS)
 Emergency Call
 Roaming
- Wireless Charging**
 Wireless charging (requires new battery cover and wireless charging dock) for ease of use



Pocket Size Design



Superior Audio

Single Pin Accessory Port

Micro USB Charging

Accessories

Included

- Li-Ion Battery
- Micro-USB Power Adapter
- Antenna (attached)
- Belt Clip
- Nylon Strap

Optional

See website for full list



Wireless Charging Kit
POA113



Rapid Rate
Charger
CH10L20



Programming Cable
(Micro USB / USB Port)
PC69



Earset C-Type
In-line Speaker / MIC
EHS16

AVAILABLE THROUGH:



Sure-Response

Tel: 888.530.5668

1075 North Reed Station Road | Carbondale, IL 62902

www.sure-response.com

Specifications

General	Frequency Range	UHF: 430-470Mz		
	Channel Capacity	256		
	Channel Spacing	25 / 12.5KHz		
	Operating Voltage	3.7V		
	Battery	2000mAh (Li-Ion)		
	Battery Life (5-5-90 Duty Cycle)	Analog	Approx. 10hrs	
		Digital	Approx. 12hrs	
	Frequency Stability	+ 0.5ppm		
	Antenna Impedance	50 Ω		
	Dimensions (HxWxD)	4.84 x 2.17 x 0.91 inches		
	Weight	5.64 oz		
	FCC ID	See Website for Full List		
	Industry Canada ID	See Website for Full List		

Environmental Specs	Operating Temperature	-22° F ~ +140° F
	Storage Temperature	-40° F ~ +185° F
	ESD	IEC 61000 - 4 - 2 (level 4) ± 8kV(contact) ; ± 15kV (air)
	American Military Standard	MIL-STD-810 C/D/E/F/G
	Dust & Water Intrusion	IP54 Standard
	Humidity	Per MIL-STD-810 C/D/E/F/G Standard
	Shock & Vibration	Per MIL-STD-810 C/D/E/F/G Standard

Transmitter	RF Power Output	1.5 - 3W
	FM Modulation (Analog Emissions Designator)	11K F3E @ 12.5KHz 16K F3E @ 25KHz
	4FSK Digital Modulation (Digital Emissions Designator)	12.5KHz Data Only: 7K6 FXD 12.5KHz Data & Voice: 7K6 FXW
	Conducted/Radiated Emission	-36dBm<1GHz -30dBm>1GHz
	Modulation Limiting	± 2.5KHz @ 12.5KHz ± 5.0KHz @ 25KHz
	FM Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
	Adjacent Channel Power	60dB @ 12.5KHz 70dB @ 25KHz
	Audio Response	+1 ~ -3dB
	Audio Distortion	≤ 3%
	Digital Protocol	ETSI-TS102 361-1, 2&3

Receiver	Sensitivity	Analog	0.22μ V (12dB SINAD) ; 0.22μ V (Typical) (12dB SINAD); 0.4μ V (20dB SINAD)
		Digital	0.22μ V/BER5%
	Selectivity TIA-603 ETSI	60dB @ 12.5KHz / 75dB @ 25KHz 60dB @ 12.5KHz / 70dB @ 25KHz	
	Intermodulation TIA-603 ETSI	70dB @ 12.5 / 25KHz 65dB @ 12.5 / 25KHz	
	Spurious Response Rejection TIA-603 ETSI	70dB @ 12.5 / 25KHz 70dB @ 12.5 / 25KHz	
	Blocking TIA-603 ETSI	80dB 84dB	
	S/N	40dB @ 12.5KHz; 43dB @ 20KHz; 45dB @ 25KHz	
	Rated Audio Power Output	0.4W	
	Rated Audio Distortion	≤ 5%	
	Audio Response	+1 ~ -3dB	
Conducted Spurious Emission	< -57dBm		



Hytera America

3315 Commerce Parkway, Miramar, FL 33025, United States
Telephone: +1(954)846-1011

8 Whatney, Suite 200, Irvine, CA 92618, United States
Telephone: +1(949)326-5740

1916 Wright Boulevard, Schaumburg, IL 60193, United States
Telephone: +1 (213) 262-3578



AVAILABLE THROUGH:

Sure-Response

Tel: 888.530.5668
1075 North Reed Station Road
Carbondale, IL 62902
www.sure-response.com



Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

HYT, Hytera are registered trademarks of Hytera Communications Corp., Ltd.
© 2018 Hytera Communications Corp., Ltd. All Rights Reserved.

EN20181107A